

Technical data sheet

Coaxial protection device for N connection: female/female

Item number: 5093988



Coaxial data cable protection devices


- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter plug), m = plug/f = female connector
- Optimised transmission behaviour
- 5-year guarantee
- With N connector
- Including OBO M25 Quick clip for simple installation



Master data

Item number	5093988
Description 1	Protective device
Description 2	for high-frequency cables
Manufacturer	OBO
Dimension	130V
Smallest sales unit	1
Unit of quantity	Piece
Weight	11.5 kg
Weight unit	kg/100 pc.

Dimensions



Technical data sheet

Coaxial protection device for N connection: female/female

Item number: 5093988



Technical data

Arrestor monitoring	no
Number of poles	1
Insertion loss	≤0,62 dB
Explosion-tested version	no
Telecommunications contact	no
Total discharge current (10/350)	5 kA
Total discharge current (8/20)	10 kA
Cut-off frequency	3000 MHz
Maximum continuous voltage AC	130 V
Maximum continuous voltage DC	185 V
Lightning impulse current	2.5 kA
Insulation resistance	>1 GΩ
Capacity (wire-wire)	<10 pF
Capacity (wire-earth)	<20 pF
Kategorie	Type 1+2 / D1+C2
Lightning protection zone LPZ	0→2
Mounting type	Connector/cable adapter
Nominal load current AC	7 A
Nominal load current DC	10 A
Testing standard	IEC 61643-21
Return loss	≥14 dB
Shielding connection available	yes
Screening	Direct
Protection rating	IP40
Protection level	<800 V
Protection level wire-wire	<800 V
Protection level wire-earth	<800 V
Signalling on device	None
SPD to IEC 61643-21	Class I+II / D1+C2
Plug-in system	N
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-40 °C
Wave resistance	50 Ω
Cable type for surge protection devices	Data cable COAX