

Technical data sheet

Hollow core anchor Easy

Item number: 3498770



Hollow core anchor "Easy" for mounting in prestressed hollow concrete slabs. When the screw or the nut is tightened, the cone is released from the anchor sleeve and pulled into it. This makes the anchor expand in the hollow space, thereby creating form lock. The hollow core anchor can also be used when the expansion area is not located in the cavity.

The fastening of the component can be done with standard screws and threaded rods.

General type approval Z-21.1-1785 granted by the German Institute for civil engineering (DIBt), Berlin, including permissible loads when exposed to fire up to a fire resistance duration of 120 minutes.

St	Steel
G	Electrogalvanized

Master data

Item number	3498770
Description 1	Hollow core anchor Easy
Manufacturer	OBO
Dimension	M8
Colour	zinc
Material	Steel
Surface	Electrogalvanized
Surface standard	EN ISO 19598 / EN ISO 4042
Smallest sales unit	25
Unit of quantity	Piece
Weight	1.5 kg
Weight unit	kg/100 pc.


Technical data sheet

Hollow core anchor Easy

Item number: 3498770



Dimensions



Length	44 mm
Dimension L	44 mm

Technical data

Drill hole depth	55 mm
Drill hole diameter, min.	12 mm
Thread	M8
Thread metric	8
With thread	yes
With bolts	no