
# **Technical data sheet**

## Cable tray, marine standard A4

**Item number: 6045854** 



Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.





**A**4

Stainless steel

2B

Bright, treated

### Master data


| Item number                           | 6045854                    |
|---------------------------------------|----------------------------|
| Description 1                         | Cable tray marine standard |
| Description 2                         | Material thickness 1.00mm  |
| Manufacturer                          | OBO                        |
| Dimension                             | 15x100x2000                |
| Colour                                | stainless steel            |
| Material                              | Stainless steel            |
| Surface                               | Bright, treated            |
| Surface standard                      |                            |
| Smallest sales unit                   | 2                          |
| Unit of quantity                      | Metre                      |
| Weight                                | 75.85 kg                   |
| Weight unit                           | kg/100 m                   |
| CO Footprint (GWP) Cradle-to-<br>Gate | 6,5624 kg COe / 1 Meter    |

# **Technical data sheet**

## Cable tray, marine standard A4







| ical data |   |                    |
|-----------|---|--------------------|
|           | Connector version                       | Without connectors |
|           | Walkable                                | no                 |
|           | Maintain electrical functions           | no                 |
|           | With cover                              | no                 |
|           | Mounting perforation in base            | yes                |
|           | NATO hole pattern                       | yes                |
|           | Rustproof steel, pickled                | yes                |
|           | Side perforation                        | no                 |
|           | Wide-span version                       | no                 |
|           | Load test type according to IEC 61537   | Type II            |
|           | Type of connector, cable support system | Screwed            |
|           |   |                    |

| Loads |                       |           |
|-------|-----------------------|-----------|
|       | Support spacing 1.0 m | 0.35 kN/m |
|       | Support spacing 1.5 m | 0.15 kN/m |