


Technical data sheet

Cable tray, marine standard FT

Item number: 6045138



Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.



- StSteel
- FTHot-dip galvanised

Master data

Item number	6045138
Description 1	Cable tray marine standard
Description 2	Material thickness 1.25mm
Manufacturer	OBO
Dimension	15x125x2000
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	2
Unit of quantity	Metre
Weight	122.45 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to-Gate	3,3143 kg COe / 1 Meter


Technical data sheet

Cable tray, marine standard FT

Item number: 6045138



Dimensions



Dimension	15 x 125
Length	2,000 mm
Width	125 mm
Height	15 mm
Plate thickness	1.25 mm
Dimension B	125 mm

Technical data

Connector version	Without connectors
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	yes
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Loads

Support spacing 1.0 m	0.6 kN/m
Support spacing 1.5 m	0.2 kN/m