
Technical data sheet

Cable tray, marine standard A2

Item number: 6045838



Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.





A2

Stainless steel

2B

Bright, treated

Master data


| Item number | 6045838 |
|---------------------------------------|----------------------------|
| Description 1 | Cable tray marine standard |
| Description 2 | Material thickness 1.50mm |
| Manufacturer | OBO |
| Dimension | 15x150x2000 |
| Colour | stainless steel |
| Material | Stainless steel |
| Surface | Bright, treated |
| Surface standard | |
| Smallest sales unit | 2 |
| Unit of quantity | Metre |
| Weight | 154.1 kg |
| Weight unit | kg/100 m |
| CO Footprint (GWP) Cradle-to- Gate | 14,6745 kg COe / 1 Meter |

Technical data sheet

Cable tray, marine standard A2







| ical data | | |
|-----------|---|--------------------|
| | Connector version | Without connectors |
| | Walkable | no |
| | Maintain electrical functions | no |
| | With cover | no |
| | Mounting perforation in base | yes |
| | NATO hole pattern | yes |
| | Rustproof steel, pickled | yes |
| | Side perforation | no |
| | Wide-span version | no |
| | Load test type according to IEC 61537 | Type II |
| | Type of connector, cable support system | Screwed |
| | ., | 1 |

| Loads | | |
|-------|-----------------------|-----------|
| | Support spacing 1.0 m | 0.75 kN/m |
| | Support spacing 1.5 m | 0.25 kN/m |