


Technical data sheet

Cable tray, marine standard, ALU

Item number: 6045774



Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.



Alu

Aluminium

Master data		
	Item number	6045774
	Description 1	Cable tray marine standard
	Description 2	Material thickness 2.00mm
	Manufacturer	OBO
	Dimension	15x250x2000
	Colour	aluminium
	Material	Aluminium
	Smallest sales unit	2
	Unit of quantity	Metre
	Weight	107.9 kg
	Weight unit	kg/100 m
	CO Footprint (GWP) Cradle-to-Gate	22,9259 kg COe / 1 Meter


Technical data sheet

Cable tray, marine standard, ALU

Item number: 6045774



Dimensions



Dimension	15 x 250
Length	2,000 mm
Width	250 mm
Height	15 mm
Plate thickness	2 mm
Dimension B	250 mm

Technical data

Connector version	Without connectors
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	yes
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Loads

Support spacing 1.0 m	0.5 kN/m
Support spacing 1.5 m	0.15 kN/m