
## Technical data sheet 45° bend 110 FS







45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.

### CER

St

Steel

FS

Strip galvanized


#### Master data

Item number	6036304
Туре	RB 45 130 FS
Description 1	45° bend
Description 2	for cable tray, horizontal
Manufacturer	OBO
Dimension	110x300
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	133.3 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	4,2067 kg CO2e / 1 Piece

# Technical data sheet 45° bend 110 FS



**Item number: 6036304** 



Width	300 mm
Height	110 mm
Plate thickness	0.8 mm
Dimension B	300 mm

### Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	22 St.
Rail thickness	1.25 mm