Technical data sheet

45° bend 85 FT

Item number: 6036238





45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 85 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.

CER

St

Steel

FT

Hot-dip galvanised

Master data

Item number	6036238
Туре	RB 45 850 FT
Description 1	45° bend
Description 2	for cable tray, horizontal
Manufacturer	OBO
Dimension	85x500
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	236 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	7,089 kg CO2e / 1 Piece

Technical data sheet

45° bend 85 FT

Item number: 6036238



Dimensions \$50 496 579

500 mm
85 mm
1 mm
500 mm

Technical data

Bend (angle) Connector version Integrated connector Type Bend, rigid Maintain electrical functions Material thickness, floor plate Vith cover Mounting perforation in base NATO hole pattern Change of direction Rustproof steel, pickled Permitted temperature range. Integrated connector Integrated
Type Bend, rigid Maintain electrical functions no Material thickness, floor plate 1 mm With cover no Mounting perforation in base yes NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
Maintain electrical functions no Material thickness, floor plate 1 mm With cover no Mounting perforation in base yes NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
Material thickness, floor plate 1 mm With cover no Mounting perforation in base yes NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
With cover no no Mounting perforation in base yes NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
Mounting perforation in base yes NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
NATO hole pattern no Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
Change of direction Horizontal Rustproof steel, pickled no Side perforation yes
Rustproof steel, pickled no yes
Side perforation yes
· · · · · · · · · · · · · · · · · · ·
Permitted temperature range 120 °C
max.
Permitted temperature range, min20 °C
Wide-span version no
Type of connector, cable support system screwed/clamped
Recommended quantity of bolts 20 St.
Rail thickness 1.25 mm