Technical data sheet 90° bend 110 FS





90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.



CER

St

Steel

FS

Strip galvanized

Master data

6036800
90° bend
for cable tray, horizontal
OBO
110x100
zinc
Steel
Strip galvanized
DIN EN 10346
1
Piece
88 kg
kg/100 pc.

Technical data sheet 90° bend 110 FS



Item number: 6036800

Dimensions 96 225

Width	100 mm
Height	110 mm
Plate thickness	0.8 mm
Dimension B	100 mm
Dimension R	50 mm

Technical data

Bend (angle)	90°
Connector version	Integrated connector
Type	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	18 St.
Rail thickness	1.25 mm