# Technical data sheet

Cover, T piece 500 A4

### Item number: 6038688



Cover for T piece fitting for lockable and screw-on cable trays in indoor and outdoor areas, to protect cables against damage and soiling. Fastening with premounted sash lock and through attachment of the section cover. Suitable for all side heights.

The cover can be used with fittings of all side heights.





A4 Stainless steel 2B Bright, treated

#### Master data

| Item number                            | 6038688                   |
|--|---------------------------|
| Туре                                   | RTD 500 A4                |
| Description 1                          | Cover                     |
| Description 2                          | for T piece               |
| Manufacturer                           | OBO                       |
| Dimension                              | B500mm                    |
| Colour                                 | stainless steel           |
| Material                               | Stainless steel           |
| Surface                                | Bright, treated           |
| Surface standard                       |                           |
| Smallest sales unit                    | 1                         |
| Unit of quantity                       | Piece                     |
| Weight                                 | 270 kg                    |
| Weight unit                            | kg/100 pc.                |
| CO2 Footprint (GWP) Cradle-to-<br>Gate | 25,2898 kg CO2e / 1 Piece |

# **Technical data sheet** Cover, T piece 500 A4

## Item number: 6038688





| Number of turn buckles            | 1 St.     |
|-----------------------------------|-----------|
| Fastening type                    | Sash lock |
| Suitable for cable ladder         | no        |
| Suitable for cable tray           | yes       |
| Material thickness                | 1 mm      |
| Rustproof steel, pickled          | no        |
| Permitted temperature range, max. | 120 °C    |
| Permitted temperature range, min. | -20 °C    |
| Wide-span version                 | no        |