## Technical data sheet Cable tray SKS 60 FS

### Item number: 6056202





SKS 60 = heavy-duty cable tray system with 60 mm side height. The cable tray, type SKS, should also be used for the maintenance of electrical function. For additional data, please refer to BSS fire protection systems. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

St Steel FS Strip galvanized

#### Master data


Item number	6056202
Туре	SKS 620 FS
Description 1	Cable tray SKS
Description 2	perforated
Manufacturer	OBO
Dimension	60x200x3000
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	366.433 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to- Gate	9,5594 kg COe / 1 Meter

# Technical data sheet Cable tray SKS 60 FS

### Item number: 6056202



### Dimensions



Dimension	60 x 200
Length	3,000 mm
Length	10 ft
Width	200 mm
Width	8 in
Height	60 mm
Height	2 in
Plate thickness	0.06 in
Plate thickness	1.5 mm
Dimension B	200 mm
Maß W	200 mm

#### **Technical data**

Connector version	Supplied connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Base perforation	7 x 32
Maintain electrical functions	yes
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	118 cm <sup>2</sup>
Usable cross-section	11800 mm <sup>2</sup>
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Туре II
Type of connector, cable support system	Screwed

## **Technical data sheet** Cable tray SKS 60 FS

### Item number: 6056202



Loads

Insertable support spacings, min.	1.5 m
Insertable support spacings, max.	3 m
Support spacing 1.5 m	2.65 kN/m
Support spacing 2.0 m	1.8 kN/m
Support spacing 2.5 m	1.15 kN/m
Support spacing 3.0 m	0.5 kN/m

#### 4 3,00 30 - 25 2,50 100-600 -20 2,00 1,50 - 15 1,00 -10 0,50 - 5 0 -**|►2** 3,0

2,25 2,5 2,75

1,75

2,0

1,5

- Permitted cable tray/ladder load in kN/m without man load 1
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
  - Load scheme during testing
  - Load curve with cable tray/ladder width in mm
  - Strut bend curve according to support width