# Technical data sheet

## Drop-in anchor for multiple fastening G

## Item number: 3492206

Drop-in anchor for multiple fastening, with internal thread in steel, for the anchoring of, for example, cable tray systems, consoles, steel conctructions, etc. in uncracked concrete in indoor and outdoor areas. To knock in with a hammer. With an edge to prevent the anchor from being pulled in. Rustproof and highly corrosion-resistant. The anchor sleeve tightens against the drill hole wall when the internal pin is knocked in, e.g. using the manual firing tool EHS M. Fire-safety tested, fire protection class R 120. European Technical Assessment ETA-07/0135 for use in concrete and European Technical Assessment ETA-07/0142 for use in concrete for redundant non-structural systems.

CE

| | |
|---|---|
| St | Steel |
| G | Electrogalvanised |

### Master data

| | |
|---|---|
| Item number | 3492206 |
| Type | EA II M 8x25 |
| Description 1 | Drop-in anchor |
| Description 2 | for multiple fastening |
| Manufacturer | OBO |
| Dimension | M8x25 |
| Colour | zinc |
| Material | Steel |
| Surface | Electrogalvanised |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| Smallest sales unit | 100 |
| Unit of quantity | Piece |
| Weight | 0.9 kg |
| Weight unit | kg/100 pc. |

# Technical data sheet

## Drop-in anchor for multiple fastening G

## Item number: 3492206

### Dimensions




| | |
|---|---|
| Length | 25 mm |
| Dimension L | 25 mm |

### Technical data

| | |
|---|---|
| Version for | Lightning strike |
| Fastening unit | Miscellaneous |
| Drill hole depth | 25 mm |
| Drill hole diameter, min. | 10 mm |
| Screw-in depth, max. | 14 mm |
| Screw-in depth, min. | 6 mm |
| Thread | M8 |
| Thread metric | 8 |
| Thread type | Metric |
| ROHS-conformant | yes |
| Self-drilling | no |
| Approvals available | yes |
| Permitted load range, tension zone | 1.4 |
| Suitable for material | Concrete Natural stone |
| Mounting type, anchor, tie | Pre-mounting |