# Technical data sheet

## Cable tray for conveyor technology 60 FS

## Item number: 6061843

Perforated cable tray for the routing of cables, especially suited for material handling technology in the automotive industry. Can be used in indoor areas. Screw connection. Suitable for direct and elevated floor mounting.

CE

| | |
|---|---|
| St | Steel |
| FS | Strip galvanised |

### Master data

| | |
|---|---|
| Item number | 6061843 |
| Type | BKRS F 620 FS |
| Description 1 | Cable Tray |
| Description 2 | for conveyor technology |
| Manufacturer | OBO |
| Dimension | 60x200x3000 |
| Colour | zinc |
| Material | Steel |
| Surface | Strip galvanised |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 3 |
| Unit of quantity | Metre |
| Weight | 366.67 kg |
| Weight unit | kg/100 m |
| CO2 Footprint (GWP) Cradle-to-Gate | 9,0882 kg CO2e / 1 Meter |

# Technical data sheet

## Cable tray for conveyor technology 60 FS

## Item number: 6061843

### Dimensions




| | |
|---|---|
| Dimension | 60x200 |
| Length | 3,000 mm |
| Width | 200 mm |
| Height | 60 mm |
| Plate thickness | 1.5 mm |
| Dimension B | 200 mm |
| Dimension H | 60 mm |

### Technical data

| | |
|---|---|
| Connector version | Without connectors |
| Maintain electrical functions | no |
| With cover | no |
| Mounting perforation in base | yes |
| NATO hole pattern | no |
| Usable cross-section | 118 cm² |
| Usable cross-section | 11800 mm² |
| ROHS-conformant | yes |
| Rustproof steel, pickled | no |
| Side perforation | no |
| Wide-span version | no |
| Usable length | 3000 mm |
| Type of connector, cable support system | Screwed |